



# BODY 715 TURBO AX

Technical Data Sheet No 301

**Product Application:** »» Add 4 caps of BODY 715 TURBO AX in 1 litre of the ready for use product

Improvement of drying time

Compatible with PU systems

Provides good mechanical and chemical resistance



After the addition make sure you mix well and spray almost immediately.



Protect from humidity



Always wear protective equipment



Always close tin after use



Follow the application instructions mentioned in this TDS

**Flash Point:**  
27°C / 92°F

**Specific Gravity:**  
0.9 g/cm<sup>3</sup>

**Solid Content (No thinner):**  
-

**VOC (2001/42/EC)**  
Not applicable

*This product is an accelerator and is not used on its own. Therefore it is not incorporated under the European legislation for Volatile Organic Compounds.*

**Theoretical Coverage:**  
-

**Cleaning of equipment:**  
Clean after final use with BODY 740 ACRYLIC SOLVENT

**Remarks:**

- Allow for additional time for combi spray booths to reach the desired temperature
- Best results when used with HB BODY PRODUCTS
- It can be used by countries that do not adopt the VOC legislation as well.

**Storage shelf life:**

- Up to 24 months storage time of unopened tins
- (+5 to +25°C)

**2K paint systems tend to react with water, hence all the equipment used must be moisture free. Isocyanates may cause skin sensitization. More specifically, care should be taken when handling the material. Anyone with a history of histaminic conditions, or respiratory problems should consult the doctor first.**

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

Issue 1/2013, April 2013