



TECHNICAL DATA SHEET

MASKING TAPE WATERPROOF 120C**GENERAL TECHNICAL DESCRIPTION**

Most premium grade automotive masking
Completely waterproof

PRODUCT APPLICATION

Wet sanding water proof
Guaranteed spray painting
Oven use in 120°C (248°F) for
30 minutes
Aircraft painting

PROPERTIES

Wet sanding
120°C (248°F) oven use for 30 minutes
Suitable for both metallic and plastic surfaces
Absolute residue free removal
Various surface options to cover special
requirements
Excellent tape to tape adhesion
Solvent and thinner resistant
Easy tear
Excellent conformability
Suitable for water and solvent based paints
Easy curving
Easy application on uneven surfaces

NOMINAL VALUES**BACKING**

Impregnated Crepe Paper

ADHESIVE

Solvent-based, Natural Rubber

TENSILE STRENGTH MD

110 ± 20 (N/25mm) TM 5004 by Afera

ELONGATION AT BREAK MD

10 ± 2 (%) TM 5004 by Afera

PEEL ADHESION ON STAINLESS STEEL

5 ± 1 (N/25mm) TM 5001 by Afera

PAPER THICKNESS

115 ± 15 (µm)

TOTAL THICKNESS

150 ± 15 (µm)

APPLICATION RANGE

120°C (248°F) for 30 minutes

PAPER COLORS

Yellow

ADHESIVE COLOR

Transparent

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

FEBRUARY 2022