

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**Trade name: **SPRAY P360 2K HS PRIMER**

Article number: B627

UFI: QA50-N020-W00A-UJVP

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Life cycle stages IS Use at industrial Sites

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

Process category PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

Environmental release category ERC5 Use at industrial site leading to inclusion into/onto article

Article category AC1 Vehicles

Technical function Other

Application of the substance / the mixture Surface protection

**1.3 Details of the supplier of the safety data sheet**

Manufacturer/Supplier:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 &amp; MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

Further information obtainable from:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 &amp; MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

**1.4 Emergency telephone number:**

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

Regional Medicines and Poisons Information Centre NI

Pharmacy Department, Royal Hospital Suite

Grosvenor Road Belfast

Telephone: +44 28 90 63 2032

Fax: +44 28 90 24 80 30

Emergency telephone: 844 892 0111

E-mail address: nirdic.nirdic@belfasttrust.hscni.net

**Trade name: SPRAY P360 2K HS PRIMER**

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

**2.2 Label elements**

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02 GHS07

Signal word Danger

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Additional information:

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

Buildup of explosive mixtures possible without sufficient ventilation.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**2.3 Other hazards**

Results of PBT and vPvB assessment

This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

PBT: Not applicable.

vPvB: Not applicable.

**SECTION 3: Composition/information on ingredients**

**3.2 Chemical characterisation: Mixtures**

Description: Mixture of hazardous substances listed below with nonhazardous additions.

Continue on page 3  
GB

**Trade name: SPRAY P360 2K HS PRIMER**
**Dangerous components:**

|                                |                                                             |          |
|--------------------------------|-------------------------------------------------------------|----------|
| CAS: 115-10-6                  | dimethyl ether                                              | 30-<35%  |
| EINECS: 204-065-8              | Flam. Gas 1A, H220                                          |          |
| Index number: 603-019-00-8     | Acute Tox. 2, H330                                          |          |
| RTECS: PM 4780000              | Press. Gas (Comp.), H280                                    |          |
| CAS: 1330-20-7                 | xylene                                                      | 10-<15%  |
| Index number: 601-022-00-9     | Flam. Liq. 3, H226                                          |          |
|                                | Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 |          |
| CAS: 123-86-4                  | n-butyl ester                                               | 5-<10%   |
| EINECS: 204-658-1              | Flam. Liq. 3, H226                                          |          |
| Index number: 607-025-00-1     | STOT SE 3, H336                                             |          |
| RTECS: AF 7350000              |                                                             |          |
| Reg.nr.: 01-2119485493-29-007  |                                                             |          |
| 01-2119485493-29-004           |                                                             |          |
| 01-2119485493-29-003           |                                                             |          |
| 01-2119485493-29-005           |                                                             |          |
| 01-2119485493-29               |                                                             |          |
| CAS: 67-64-1                   | acetone                                                     | 5-<10%   |
| EINECS: 200-662-2              | Flam. Liq. 2, H225                                          |          |
| Index number: 606-001-00-8     | Eye Irrit. 2, H319; STOT SE 3, H336                         |          |
| RTECS: AL 3150000              |                                                             |          |
| Reg.nr.: 01-2119471330-49-0001 |                                                             |          |
| CAS: 13463-67-7                | titanium dioxide                                            | 1-<5%    |
| EINECS: 236-675-5              | Carc. 2, H351                                               |          |
| Index number: 022-006-00-2     | Note: V, W, 10                                              |          |
| CAS: 64742-95-6                | Solvent naphtha (petroleum), light arom.                    | ≥1-<2.5% |
| EINECS: 265-199-0              | Flam. Liq. 3, H226                                          |          |
| Index number: 649-356-00-4     | Asp. Tox. 1, H304                                           |          |
| Reg.nr.: 01-2119455851-35-0001 | Aquatic Chronic 2, H411                                     |          |
|                                | Acute Tox. 4, H332; STOT SE 3, H335                         |          |
|                                | STOT SE 3, H336                                             |          |
|                                | Note: H, P, 4                                               |          |
| CAS: 71-36-3                   | butan-1-ol                                                  | ≥1-<3%   |
| EINECS: 200-751-6              | Flam. Liq. 3, H226                                          |          |
| Index number: 603-004-00-6     | Eye Dam. 1, H318                                            |          |
| RTECS: EO 1400000              | Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335    |          |
| Reg.nr.: 01-2119484630-38-0000 | STOT SE 3, H336                                             |          |

Additional information: For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**
**4.1 Description of first aid measures**

General information: Immediately remove any clothing soiled by the product.

After inhalation: In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Remove contact lenses in case of eye contamination and irrigate copiously with clean water for at least 15 minutes trying to hold the eye lids open.

After swallowing: If symptoms persist consult doctor.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## **Trade name: SPRAY P360 2K HS PRIMER**

### **SECTION 5: Firefighting measures**

#### **5.1 Extinguishing media**

Suitable extinguishing agents:

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**5.2 Special hazards arising from the substance or mixture** No further relevant information available.

#### **5.3 Advice for firefighters**

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

#### **5.6 Fire and explosion Hazards**

Speial protective equipment and fire fighting procedures:

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

### **SECTION 6: Accidental release measures**

#### **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.

#### **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

**7.1 Precautions for safe handling** No special precautions are necessary if used correctly.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

#### **7.2 Conditions for safe storage, including any incompatibilities**

Storage:

Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep container tightly sealed.

**7.3 Specific end use(s)** No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

#### **8.1 Control parameters**

Ingredients with limit values that require monitoring at the workplace:

##### **115-10-6 dimethyl ether**

WEL Short-term value: 958 mg/m<sup>3</sup>, 500 ppm

Long-term value: 766 mg/m<sup>3</sup>, 400 ppm

##### **1330-20-7 xylene**

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm

Long-term value: 220 mg/m<sup>3</sup>, 50 ppm

Sk; BMGV

## **Trade name: SPRAY P360 2K HS PRIMER**

### **123-86-4 n-butyl ester**

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

### **67-64-1 acetone**

WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm  
Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

### **71-36-3 butan-1-ol**

WEL Short-term value: 154 mg/m<sup>3</sup>, 50 ppm  
Sk

- Regulatory information WEL: EH40/2020
- DNELs

### **ATE (Acute Toxicity Estimates)**

Inhalative DNELs >68 mg/m<sup>3</sup>

### **1330-20-7 xylene**

Inhalative DNELs 11 mg/m<sup>3</sup> (ATE)

- Ingredients with biological limit values:

### **1330-20-7 xylene**

BMGV 650 mmol/mol creatinine  
Medium: urine  
Sampling time: post shift  
Parameter: methyl hippuric acid

- Additional information: The lists valid during the making were used as basis.

### **8.2 Exposure controls**

- Personal protective equipment:
- General protective and hygienic measures:  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the basis of the different substances in the preparation.

- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:  
Rubber gloves

Continue on page 6  
GB

**Trade name: SPRAY P360 2K HS PRIMER**

- Eye protection:  
Safety glasses



Tightly sealed goggles

- Body protection: Protective work clothing

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

· General Information

· Appearance:

Form: Aerosol  
Colour: According to product specification

· Odour: Characteristic

· Odour threshold: Not determined.

· pH-value: Mixture is non-soluble (in water).

· Change in condition

Melting point/freezing point: Undetermined.  
Initial boiling point and boiling range: -24.9 °C (115-10-6 dimethyl ether)

· Flash point: < 0 °C

· Flammability: Not applicable.

· Autoignition temperature: 235 °C (115-10-6 dimethyl ether)

· Decomposition temperature: Not determined.

· Ignition temperature: Product is not selfigniting.

· Explosive properties: Risk of explosion by shock, friction, fire or other sources of ignition.

· Explosion limits:

Lower: 3 Vol % (115-10-6 dimethyl ether)  
Upper: 18.6 Vol % (115-10-6 dimethyl ether)

· Vapour pressure at 20 °C: 5,200 hPa (115-10-6 dimethyl ether)

· Density at 20 °C: 0.95 g/cm<sup>3</sup>

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not applicable.

· Solubility in / Miscibility with  
water:

Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.  
Kinematic at 20 °C: 0 mm<sup>2</sup>/s

· Solvent content:

Organic solvents: 63.8 %  
VOC (EC) 605.8 g/l  
Solids content (volume): 27.0 %

**9.2 Other information**

No further relevant information available.

**Trade name:** **SPRAY P360 2K HS PRIMER**

## **SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
  - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

- **11.1 Information on toxicological effects**
  - Acute toxicity Based on available data, the classification criteria are not met.
  - LD/LC50 values relevant for classification:

### **ATE (Acute Toxicity Estimates)**

Oral LD50 43,996 mg/kg (rat)  
Dermal LD50 14,395 mg/kg

### **115-10-6 dimethyl ether**

Inhalative LC50/4 h 308 mg/l (rat)

### **471-34-1 calcium carbonate**

Oral LD50 6,450 mg/kg (rat)

### **1330-20-7 xylene**

Oral LD50 4,300 mg/kg (rat)  
Dermal LD50 2,000 mg/kg (rabbit)

### **123-86-4 n-butyl ester**

Oral LD50 13,100 mg/kg (rat)  
Dermal LD50 >5,000 mg/kg (rabbit)  
Inhalative LC50/4 h >21 mg/l (rat)

### **67-64-1 acetone**

Oral LD50 5,800 mg/kg (rat)  
Dermal LD50 20,000 mg/kg (rabbit)

### **13463-67-7 titanium dioxide**

Oral LD50 >20,000 mg/kg (rat)  
Dermal LD50 >10,000 mg/kg (rabbit)  
Inhalative LC50/4 h >6.82 mg/l (rat)

### **64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral LD50 >6,800 mg/kg (rat)  
Dermal LD50 >3,400 mg/kg (rab)  
Inhalative LC50/4 h >10.2 mg/l (rat)

### **71-36-3 butan-1-ol**

Oral LD50 790 mg/kg (rat)  
Dermal LD50 3,400 mg/kg (rabbit)  
Inhalative LC50/4 h 8,000 mg/l (rat)

- Primary irritant effect:
- Skin corrosion/irritation  
Causes skin irritation.
- Serious eye damage/irritation  
Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Continue on page 8  
GB

**Trade name: SPRAY P360 2K HS PRIMER**

- Additional toxicological information:
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information**

- **12.1 Toxicity**
- Aquatic toxicity:  
This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea
- **12.2 Persistence and degradability**  
This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Additional ecological information:
- General notes:  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
- vPvB: Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- Recommendation  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **European waste catalogue**
- HP3 Flammable
- HP4 Irritant - skin irritation and eye damage
- HP7 Carcinogenic
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

**SECTION 14: Transport information**

- **14.1 UN-Number**
- ADR, IMDG, IATA UN1950
- **14.2 UN proper shipping name**
- ADR UN1950 AEROSOLS
- IMDG AEROSOLS
- IATA AEROSOLS, flammable

Continue on page 9  
GB

**Trade name: SPRAY P360 2K HS PRIMER**

**14.3 Transport hazard class(es)**

· ADR



· Class  
· Label

2 5F Gases.  
2.1

· IMDG, IATA



· Class  
· Label

2.1 Gases.  
2.1

**14.4 Packing group**

· ADR, IMDG, IATA

Void

**14.5 Environmental hazards:**

Not applicable.

**14.6 Special precautions for user**

Warning: Gases.

· Hazard identification number (Kemler code):

-

· EMS Number:

F-D,S-U

· Stowage Code

SW1 Protected from sources of heat.  
SW22 For AEROSOLS with a maximum capacity of 1 litre:  
Category A. For AEROSOLS with a capacity above 1 litre:  
Category B. For WASTE AEROSOLS: Category C, Clear of  
living quarters.  
SG69 For AEROSOLS with a maximum capacity of 1 litre:  
Segregation as for class 9. Stow "separated from" class 1  
except for division 1.4.  
For AEROSOLS with a capacity above 1 litre:  
Segregation as for the appropriate subdivision of class 2.  
For WASTE AEROSOLS:  
Segregation as for the appropriate subdivision of class 2.

· Segregation Code

**14.7 Transport in bulk according to Annex II  
of Marpol and the IBC Code**

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E0  
Not permitted as Excepted Quantity

· Transport category

2

· Tunnel restriction code

D

· IMDG

· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E0  
Not permitted as Excepted Quantity

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or  
mixture**

None of the ingredients is listed.

Continue on page 10  
GB

**Trade name: SPRAY P360 2K HS PRIMER**

- Poisons Act
- Regulated explosives precursors  
None of the ingredients is listed.
- Regulated poisons  
None of the ingredients is listed.
- Reportable explosives precursors  
67-64-1 acetone: Listed
- Reportable poisons  
None of the ingredients is listed.
- Labelling according to Regulation (EC) No 1272/2008  
The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



GHS02 GHS07

- Signal word Danger
- Hazard statements  
H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.
- Precautionary statements  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P280 Wear protective gloves / eye protection / face protection.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II  
None of the ingredients is listed.
- REGULATION (EU) 2019/1148
- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))  
None of the ingredients is listed.
- Annex II - REPORTABLE EXPLOSIVES PRECURSORS  
67-64-1 acetone
- Regulation (EC) No 273/2004 on drug precursors  
67-64-1 acetone: 3
- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors  
67-64-1 acetone: 3

**Trade name: SPRAY P360 2K HS PRIMER**

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

\*

**SECTION 16: Other information**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H330 Fatal if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H411 Toxic to aquatic life with long lasting effects.
- **Classification according to Regulation (EC) No 1272/2008**

|                               |                                                                                      |
|-------------------------------|--------------------------------------------------------------------------------------|
| Aerosols, Section 2.3.1       | Bridging principles                                                                  |
| Skin corrosion/irritation     | The classification of the mixture is generally based on the calculation method using |
| Serious eye damage/irritation | substance data according to Regulation (EC) No 1272/2008.                            |

- **Contact:**  
HB BODY S.A  
Regulatory Officer  
Ms Athina Kapourani  
Ph: +30 2310 790000  
email: a.kapourani@hbbody.com

- \* Data compared to the previous version altered.

**Trade name: SPRAY P360 2K HS PRIMER**

**Annex: Exposure scenario**

**Short title of the exposure scenario**

**Sector of Use**

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**Product category** PC9a Coatings and paints, thinners, paint removers

**Process category** PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

**Article category** AC1 Vehicles

**Environmental release category** ERC5 Use at industrial site leading to inclusion into/onto article

**Technical function** Other

**Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

**Conditions of use** According to directions for use.

**Duration and frequency** Frequency of use:

**Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

**Physical state** Aerosol

**Concentration of the substance in the mixture** The substance is main component.

**Used amount per time or activity** Smaller than 100 g per application.

**Other operational conditions**

**Other operational conditions affecting environmental exposure**

No special measures required.

Use only on hard ground.

**Other operational conditions affecting worker exposure**

Avoid contact with the skin.

Do not breathe aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Avoid contact with eyes.

**Other operational conditions affecting consumer exposure** No special measures required.

**Other operational conditions affecting consumer exposure during the use of the product**

Not applicable.

**Risk management measures**

**Worker protection**

**Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

**Technical protective measures**

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Use product only in enclosed systems.

**Personal protective measures**

Avoid contact with the skin.

Use suitable respiratory protective device in case of insufficient ventilation.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Avoid contact with the eyes.

Tightly sealed goggles

**Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

**Trade name: SPRAY P360 2K HS PRIMER**· **Environmental protection measures**· **Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Do not allow to reach sewage system.

· **Soil**

The product is only processed over the concrete collecting basin.

Prevent contamination of soil.

· **Disposal measures** Ensure that waste is collected and contained.· **Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging· **Exposure estimation**· **Consumer**

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

The highest inhalative exposure to be expected for consumers is 500 ppm.

The highest dermal exposure to be expected for consumers is 2.000 mg / kg / day.

The highest oral exposure to be expected for consumers is 4300 mg / kg / day.

· **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.